Intrinsically safe sensors for zone 0/20 | IGEXPa 05

- Intrinsically safe sensors for zone 0/20
- With ATEX- and IECEx-certification
- Amplifier IKMb... is required for operation
- For use under rough climatic conditions down to -60 °C
- Connection: 2 m FEP-cable
- Waterproof up to 30 m (IP 68) and resistant to high-pressure cleaning (IP 69)
- For use in refrigeration systems and cooling processes and outdoor areas



M18x1 - sn 5 mm flush

TYPE	IGEXPa 05
Product ID	P31408
Thread/sleeve	M18x1
Operating Distance sn	5 mm flush
Ex area uf use	Zone 0, Zone 1, Zone 20, Zone 21
ATEX Certificate	EPS 17 ATEX 1 173 X
IECEx Certificate	IECEx EPS 17.0087X
UKEX Certificate	EPS 22 UKEX 1 139 X
ATEX marking gas	Ex II 1G Ex ia IIC T6...T3 Ga
ATEX Marking dust	Ex II 1D Ex ia IIIC T_{200}65°C Da
IECEx marking gas	Ex ia IIC T6...T3 Ga
IECEx marking dust	Ex ia IIIC T_{200}65°C Da
Ambient temperature gas zone 0 T6	-60 °C ... 60 °C
Ambient temperature gas zone 0 T5	-60 °C ... 60 °C
Ambient temperature gas zone 0 T4	-60 °C ... 60 °C
Ambient temperature gas zone 0 T3	-60 °C ... 60 °C
Ambient temperature dust in zone 20	-60 °C ... 60 °C

EGE-ELEKTRONIK SPEZIAL-SENSOREN GMBH

TEL. +49 4346 41580 . ege-elektronik.com

Maximum values	Ui = 12.6 V / Ii =15.9 mA / Pi = 50 mW / Ci = 66.2 nF / Li = 1.2 mH
Material housing	stainless steel AISI 316 Ti, PTFE, PVDF
Protection [EN 60529]	IP 68 (3 bar), IP 69
Electrical connection	2 m FEP-cable 2x0.34 mm²
Note	with longer cable available on request

Technical Image



Pin Map

